



power contactor, AC-3e/AC-3, 65 A, 30 kW / 400 V, 3-pole, 175-280 V AC/DC, 50/60 Hz, with integrated varistor, auxiliary contacts: 1 NO + 1 NC, main circuit: screw terminal, control and auxiliary circuit: spring-loaded terminal, size: S2,

|                                                                                                              |                                                                                                                                                                                    |
|--------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| product brand name                                                                                           | SIRIUS                                                                                                                                                                             |
| product designation                                                                                          | Power contactor                                                                                                                                                                    |
| product type designation                                                                                     | 3RT2                                                                                                                                                                               |
| <b>General technical data</b>                                                                                |                                                                                                                                                                                    |
| size of contactor                                                                                            | S2                                                                                                                                                                                 |
| product extension                                                                                            |                                                                                                                                                                                    |
| • function module for communication                                                                          | No                                                                                                                                                                                 |
| • auxiliary switch                                                                                           | Yes                                                                                                                                                                                |
| power loss [W] for rated value of the current                                                                |                                                                                                                                                                                    |
| • at AC in hot operating state                                                                               | 11.4 W                                                                                                                                                                             |
| • at AC in hot operating state per pole                                                                      | 3.8 W                                                                                                                                                                              |
| • without load current share typical                                                                         | 1 W                                                                                                                                                                                |
| type of calculation of power loss current-dependent                                                          | quadratic                                                                                                                                                                          |
| insulation voltage                                                                                           |                                                                                                                                                                                    |
| • of main circuit with degree of pollution 3 rated value                                                     | 690 V                                                                                                                                                                              |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                                                                                                                                                                              |
| surge voltage resistance                                                                                     |                                                                                                                                                                                    |
| • of main circuit rated value                                                                                | 6 kV                                                                                                                                                                               |
| • of auxiliary circuit rated value                                                                           | 6 kV                                                                                                                                                                               |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V                                                                                                                                                                              |
| shock resistance at rectangular impulse                                                                      |                                                                                                                                                                                    |
| • at AC                                                                                                      | 7.7 g / 5 ms, 4.5 g / 10 ms                                                                                                                                                        |
| • at DC                                                                                                      | 7.7 g / 5 ms, 4.5 g / 10 ms                                                                                                                                                        |
| shock resistance with sine pulse                                                                             |                                                                                                                                                                                    |
| • at AC                                                                                                      | 12 g / 5 ms, 7 g / 10 ms                                                                                                                                                           |
| • at DC                                                                                                      | 12 g / 5 ms, 7 g / 10 ms                                                                                                                                                           |
| mechanical service life (operating cycles)                                                                   |                                                                                                                                                                                    |
| • of contactor typical                                                                                       | 10 000 000                                                                                                                                                                         |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                                                                                                                                                                          |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                                                                                                                                                                         |
| reference code according to IEC 81346-2                                                                      | Q                                                                                                                                                                                  |
| Substance Prohibitance (day/month/year)                                                                      | 10/01/2014                                                                                                                                                                         |
| SVHC substance name                                                                                          | Lead CAS-No. 7439-92-1<br>Lead monoxide (lead oxide) CAS-No. 1317-36-8<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5<br>Melamine CAS-No. 108-78-1 |
| Net Weight                                                                                                   | 1.083 kg                                                                                                                                                                           |
| <b>Ambient conditions</b>                                                                                    |                                                                                                                                                                                    |

|                                                                        |                    |
|------------------------------------------------------------------------|--------------------|
| installation altitude at height above sea level maximum                | 2 000 m            |
| <b>ambient temperature</b>                                             |                    |
| • during operation                                                     | -25 ... +60 °C     |
| • during storage                                                       | -55 ... +80 °C     |
| <b>relative humidity minimum</b>                                       | 10 %               |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>  | 95 %               |
| <b>Main circuit</b>                                                    |                    |
| <b>number of poles for main current circuit</b>                        | 3                  |
| <b>number of NO contacts for main contacts</b>                         | 3                  |
| <b>number of NC contacts for main contacts</b>                         | 0                  |
| <b>operating voltage</b>                                               |                    |
| • at AC-3 rated value maximum                                          | 690 V              |
| • at AC-3e rated value maximum                                         | 690 V              |
| <b>operational current</b>                                             |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 80 A               |
| • at AC-1                                                              |                    |
| — up to 690 V at ambient temperature 40 °C rated value                 | 80 A               |
| — up to 690 V at ambient temperature 60 °C rated value                 | 70 A               |
| • at AC-3                                                              |                    |
| — at 400 V rated value                                                 | 65 A               |
| — at 500 V rated value                                                 | 65 A               |
| — at 690 V rated value                                                 | 47 A               |
| • at AC-3e                                                             |                    |
| — at 400 V rated value                                                 | 65 A               |
| — at 500 V rated value                                                 | 65 A               |
| — at 690 V rated value                                                 | 47 A               |
| • at AC-4 at 400 V rated value                                         | 55 A               |
| • at AC-5a up to 690 V rated value                                     | 70.4 A             |
| • at AC-5b up to 400 V rated value                                     | 53.9 A             |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=20 rated value                  | 56.9 A             |
| — up to 400 V for current peak value n=20 rated value                  | 56.9 A             |
| — up to 500 V for current peak value n=20 rated value                  | 56.9 A             |
| — up to 690 V for current peak value n=20 rated value                  | 47 A               |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=30 rated value                  | 38 A               |
| — up to 400 V for current peak value n=30 rated value                  | 38 A               |
| — up to 500 V for current peak value n=30 rated value                  | 38 A               |
| — up to 690 V for current peak value n=30 rated value                  | 38 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 25 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                    |
| • at 400 V rated value                                                 | 28 A               |
| • at 690 V rated value                                                 | 22 A               |
| <b>operational current</b>                                             |                    |
| • <b>at 1 current path at DC-1</b>                                     |                    |
| — at 24 V rated value                                                  | 55 A               |
| — at 60 V rated value                                                  | 23 A               |
| — at 110 V rated value                                                 | 4.5 A              |
| — at 220 V rated value                                                 | 1 A                |
| — at 440 V rated value                                                 | 0.4 A              |
| — at 600 V rated value                                                 | 0.25 A             |
| • <b>with 2 current paths in series at DC-1</b>                        |                    |
| — at 24 V rated value                                                  | 55 A               |
| — at 60 V rated value                                                  | 45 A               |
| — at 110 V rated value                                                 | 45 A               |

|                                                                         |                                                             |
|-------------------------------------------------------------------------|-------------------------------------------------------------|
| — at 220 V rated value                                                  | 5 A                                                         |
| — at 440 V rated value                                                  | 1 A                                                         |
| — at 600 V rated value                                                  | 0.8 A                                                       |
| ● <b>with 3 current paths in series at DC-1</b>                         |                                                             |
| — at 24 V rated value                                                   | 55 A                                                        |
| — at 60 V rated value                                                   | 55 A                                                        |
| — at 110 V rated value                                                  | 55 A                                                        |
| — at 220 V rated value                                                  | 45 A                                                        |
| — at 440 V rated value                                                  | 2.9 A                                                       |
| — at 600 V rated value                                                  | 1.4 A                                                       |
| ● <b>at 1 current path at DC-3 at DC-5</b>                              |                                                             |
| — at 24 V rated value                                                   | 35 A                                                        |
| — at 60 V rated value                                                   | 6 A                                                         |
| — at 220 V rated value                                                  | 1 A                                                         |
| — at 440 V rated value                                                  | 0.1 A                                                       |
| — at 600 V rated value                                                  | 0.06 A                                                      |
| ● <b>with 2 current paths in series at DC-3 at DC-5</b>                 |                                                             |
| — at 24 V rated value                                                   | 55 A                                                        |
| — at 60 V rated value                                                   | 45 A                                                        |
| — at 110 V rated value                                                  | 25 A                                                        |
| — at 220 V rated value                                                  | 5 A                                                         |
| — at 440 V rated value                                                  | 0.27 A                                                      |
| — at 600 V rated value                                                  | 0.16 A                                                      |
| ● <b>with 3 current paths in series at DC-3 at DC-5</b>                 |                                                             |
| — at 24 V rated value                                                   | 55 A                                                        |
| — at 60 V rated value                                                   | 55 A                                                        |
| — at 110 V rated value                                                  | 55 A                                                        |
| — at 220 V rated value                                                  | 25 A                                                        |
| — at 440 V rated value                                                  | 0.6 A                                                       |
| — at 600 V rated value                                                  | 0.35 A                                                      |
| <b>operating power</b>                                                  |                                                             |
| ● at AC-2 at 400 V rated value                                          | 30 kW                                                       |
| ● at AC-3                                                               |                                                             |
| — at 230 V rated value                                                  | 18.5 kW                                                     |
| — at 400 V rated value                                                  | 30 kW                                                       |
| — at 500 V rated value                                                  | 37 kW                                                       |
| — at 690 V rated value                                                  | 37 kW                                                       |
| ● at AC-3e                                                              |                                                             |
| — at 230 V rated value                                                  | 18.5 kW                                                     |
| — at 400 V rated value                                                  | 30 kW                                                       |
| — at 500 V rated value                                                  | 37 kW                                                       |
| — at 690 V rated value                                                  | 37 kW                                                       |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>      |                                                             |
| ● at 400 V rated value                                                  | 14.7 kW                                                     |
| ● at 690 V rated value                                                  | 20 kW                                                       |
| <b>operating apparent power at AC-6a</b>                                |                                                             |
| ● up to 230 V for current peak value n=20 rated value                   | 22.6 kVA                                                    |
| ● up to 400 V for current peak value n=20 rated value                   | 39.4 kVA                                                    |
| ● up to 500 V for current peak value n=20 rated value                   | 49.2 kVA                                                    |
| ● up to 690 V for current peak value n=20 rated value                   | 56.1 kVA                                                    |
| <b>operating apparent power at AC-6a</b>                                |                                                             |
| ● up to 230 V for current peak value n=30 rated value                   | 15.1 kVA                                                    |
| ● up to 400 V for current peak value n=30 rated value                   | 26.2 kVA                                                    |
| ● up to 500 V for current peak value n=30 rated value                   | 32.8 kVA                                                    |
| ● up to 690 V for current peak value n=30 rated value                   | 45.3 kVA                                                    |
| <b>short-time withstand current in cold operating state up to 40 °C</b> |                                                             |
| ● limited to 1 s switching at zero current maximum                      | 1 055 A; Use minimum cross-section acc. to AC-1 rated value |

|                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• limited to 5 s switching at zero current maximum</li> <li>• limited to 10 s switching at zero current maximum</li> <li>• limited to 30 s switching at zero current maximum</li> <li>• limited to 60 s switching at zero current maximum</li> </ul> | 730 A; Use minimum cross-section acc. to AC-1 rated value<br>520 A; Use minimum cross-section acc. to AC-1 rated value<br>336 A; Use minimum cross-section acc. to AC-1 rated value<br>272 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b>                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>                                                                                                                                                                                                                  | 1 500 1/h<br>1 500 1/h                                                                                                                                                                                                                           |
| <b>operating frequency</b>                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at AC-1 maximum</li> <li>• at AC-2 maximum</li> <li>• at AC-3 maximum</li> <li>• at AC-3e</li> <li>— maximum</li> <li>• at AC-4 maximum</li> </ul>                                                                                                 | 800 1/h<br>400 1/h<br>700 1/h<br>700 1/h<br>200 1/h                                                                                                                                                                                              |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                  |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                                        | AC/DC                                                                                                                                                                                                                                            |
| <b>control supply voltage at AC</b>                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul>                                                                                                                                                                                    | 175 ... 280 V<br>175 ... 280 V                                                                                                                                                                                                                   |
| <b>control supply voltage at DC rated value</b>                                                                                                                                                                                                                                             | 175 ... 280 V                                                                                                                                                                                                                                    |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b>                                                                                                                                                                                                       |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• initial value</li> <li>• full-scale value</li> </ul>                                                                                                                                                                                               | 0.8<br>1.1                                                                                                                                                                                                                                       |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b>                                                                                                                                                                                                       |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                            | 0.8 ... 1.1<br>0.8 ... 1.1                                                                                                                                                                                                                       |
| <b>design of the surge suppressor</b>                                                                                                                                                                                                                                                       | with varistor                                                                                                                                                                                                                                    |
| <b>inrush current peak</b>                                                                                                                                                                                                                                                                  | 5 A                                                                                                                                                                                                                                              |
| <b>duration of inrush current peak</b>                                                                                                                                                                                                                                                      | 30 µs                                                                                                                                                                                                                                            |
| <b>pickup current mean value</b>                                                                                                                                                                                                                                                            | 0.2 A                                                                                                                                                                                                                                            |
| <b>pickup current peak</b>                                                                                                                                                                                                                                                                  | 0.42 A                                                                                                                                                                                                                                           |
| <b>duration of pickup current</b>                                                                                                                                                                                                                                                           | 230 ms                                                                                                                                                                                                                                           |
| <b>holding current mean value</b>                                                                                                                                                                                                                                                           | 6 mA                                                                                                                                                                                                                                             |
| <b>apparent pick-up power of magnet coil at AC</b>                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                            | 40 V·A<br>40 V·A                                                                                                                                                                                                                                 |
| <b>apparent holding power</b>                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at minimum rated control supply voltage at DC</li> <li>• at maximum rated control supply voltage at DC</li> </ul>                                                                                                                                  | 2 V·A<br>2 V·A                                                                                                                                                                                                                                   |
| <b>apparent holding power</b>                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at minimum rated control supply voltage at AC</li> <li>— at 50 Hz</li> <li>— at 60 Hz</li> <li>• at maximum rated control supply voltage at AC</li> <li>— at 50 Hz</li> <li>— at 60 Hz</li> </ul>                                                  | 2 V·A<br>2 V·A<br>2 V·A<br>2 V·A                                                                                                                                                                                                                 |
| <b>apparent holding power of magnet coil at AC</b>                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                            | 2 V·A<br>2 V·A                                                                                                                                                                                                                                   |
| <b>inductive power factor with the holding power of the coil</b>                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                            | 0.95<br>0.95                                                                                                                                                                                                                                     |
| <b>closing power of magnet coil at DC</b>                                                                                                                                                                                                                                                   | 23 W                                                                                                                                                                                                                                             |
| <b>holding power of magnet coil at DC</b>                                                                                                                                                                                                                                                   | 1 W                                                                                                                                                                                                                                              |
| <b>closing delay</b>                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>                                                                                                                                                                                                                  | 35 ... 110 ms<br>35 ... 110 ms                                                                                                                                                                                                                   |

|                                                                                                           |                                                                                                                                      |
|-----------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>opening delay</b>                                                                                      |                                                                                                                                      |
| • at AC                                                                                                   | 30 ... 55 ms                                                                                                                         |
| • at DC                                                                                                   | 30 ... 55 ms                                                                                                                         |
| <b>arcing time</b>                                                                                        | 10 ... 20 ms                                                                                                                         |
| <b>control version of the switch operating mechanism</b>                                                  | Standard A1 - A2                                                                                                                     |
| <b>Auxiliary circuit</b>                                                                                  |                                                                                                                                      |
| number of NC contacts for auxiliary contacts instantaneous contact                                        | 1                                                                                                                                    |
| number of NO contacts for auxiliary contacts instantaneous contact                                        | 1                                                                                                                                    |
| operational current at AC-12 maximum                                                                      | 10 A                                                                                                                                 |
| <b>operational current at AC-15</b>                                                                       |                                                                                                                                      |
| • at 230 V rated value                                                                                    | 10 A                                                                                                                                 |
| • at 400 V rated value                                                                                    | 3 A                                                                                                                                  |
| • at 500 V rated value                                                                                    | 2 A                                                                                                                                  |
| • at 690 V rated value                                                                                    | 1 A                                                                                                                                  |
| <b>operational current at DC-12</b>                                                                       |                                                                                                                                      |
| • at 24 V rated value                                                                                     | 10 A                                                                                                                                 |
| • at 48 V rated value                                                                                     | 6 A                                                                                                                                  |
| • at 60 V rated value                                                                                     | 6 A                                                                                                                                  |
| • at 110 V rated value                                                                                    | 3 A                                                                                                                                  |
| • at 125 V rated value                                                                                    | 2 A                                                                                                                                  |
| • at 220 V rated value                                                                                    | 1 A                                                                                                                                  |
| • at 600 V rated value                                                                                    | 0.15 A                                                                                                                               |
| <b>operational current at DC-13</b>                                                                       |                                                                                                                                      |
| • at 24 V rated value                                                                                     | 10 A                                                                                                                                 |
| • at 48 V rated value                                                                                     | 2 A                                                                                                                                  |
| • at 60 V rated value                                                                                     | 2 A                                                                                                                                  |
| • at 110 V rated value                                                                                    | 1 A                                                                                                                                  |
| • at 125 V rated value                                                                                    | 0.9 A                                                                                                                                |
| • at 220 V rated value                                                                                    | 0.3 A                                                                                                                                |
| • at 600 V rated value                                                                                    | 0.1 A                                                                                                                                |
| <b>contact reliability of auxiliary contacts</b>                                                          | 1 faulty switching per 100 million (17 V, 1 mA)                                                                                      |
| <b>UL/CSA ratings</b>                                                                                     |                                                                                                                                      |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                                       |                                                                                                                                      |
| • at 480 V rated value                                                                                    | 65 A                                                                                                                                 |
| • at 600 V rated value                                                                                    | 52 A                                                                                                                                 |
| <b>yielded mechanical performance [hp]</b>                                                                |                                                                                                                                      |
| • for single-phase AC motor                                                                               |                                                                                                                                      |
| — at 110/120 V rated value                                                                                | 5 hp                                                                                                                                 |
| — at 230 V rated value                                                                                    | 10 hp                                                                                                                                |
| • for 3-phase AC motor                                                                                    |                                                                                                                                      |
| — at 200/208 V rated value                                                                                | 20 hp                                                                                                                                |
| — at 220/230 V rated value                                                                                | 20 hp                                                                                                                                |
| — at 460/480 V rated value                                                                                | 50 hp                                                                                                                                |
| — at 575/600 V rated value                                                                                | 50 hp                                                                                                                                |
| <b>contact rating of auxiliary contacts according to UL</b>                                               | A600 / P600                                                                                                                          |
| <b>Short-circuit protection</b>                                                                           |                                                                                                                                      |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V | C characteristic: 10 A; 0.4 kA                                                                                                       |
| <b>design of the fuse link</b>                                                                            |                                                                                                                                      |
| • for short-circuit protection of the main circuit                                                        |                                                                                                                                      |
| — with type of coordination 1 required                                                                    | gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)                                                     |
| — with type of coordination 2 required                                                                    | gG: 125 A (690 V, 100 kA), aM: 63 A (690 V, 100 kA), BS88: 100 A (415 V, 80 kA)                                                      |
| • for short-circuit protection of the auxiliary switch required                                           | gG: 10 A (500 V, 1 kA)                                                                                                               |
| <b>Installation/ mounting/ dimensions</b>                                                                 |                                                                                                                                      |
| <b>mounting position</b>                                                                                  | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fastening method side-by-side mounting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Yes                                                                                                                                                              |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                                                         |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 114 mm                                                                                                                                                           |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 55 mm                                                                                                                                                            |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 130 mm                                                                                                                                                           |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                                    |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                  |
| <b>type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>                                                                                                                                                                                                                                                                                                                            | screw-type terminals<br>spring-loaded terminals<br>Spring-type terminals<br>Spring-loaded terminal                                                               |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for main contacts</li> </ul>                                                                                                                                                                                                                                                                                  | 2x (1 ... 35 mm <sup>2</sup> ), 1x (1 ... 50 mm <sup>2</sup> )<br>2x (1 ... 25 mm <sup>2</sup> ), 1x (1 ... 35 mm <sup>2</sup> )<br>2x (18 ... 2), 1x (18 ... 1) |
| <b>connectable conductor cross-section for main contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1 ... 35 mm <sup>2</sup>                                                                                                                                         |
| <b>connectable conductor cross-section for auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> <li>• finely stranded without core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                              | 0.5 ... 2.5 mm <sup>2</sup><br>0.5 ... 1.5 mm <sup>2</sup><br>0.5 ... 2.5 mm <sup>2</sup>                                                                        |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> <li>• for AWG cables for auxiliary contacts</li> </ul>                                                                                                                                                                                                                 | 2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 14)                                    |
| <b>AWG number as coded connectable conductor cross section for main contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                              | 18 ... 1                                                                                                                                                         |
| <b>AWG number as coded connectable conductor cross section for auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                         | 20 ... 14                                                                                                                                                        |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                  |
| <b>product function</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> <li>• positively driven operation according to IEC 60947-5-1</li> <li>• suitable for safety function</li> </ul>                                                                                                                                                                                                                                                                                                                       | Yes<br>No<br>Yes                                                                                                                                                 |
| <b>suitability for use safety-related switching OFF</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Yes                                                                                                                                                              |
| <b>service life maximum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 20 a                                                                                                                                                             |
| <b>test wear-related service life necessary</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Yes                                                                                                                                                              |
| <b>proportion of dangerous failures</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                                                         | 40 %<br>73 %                                                                                                                                                     |

|                                                               |                                                  |
|---------------------------------------------------------------|--------------------------------------------------|
| B10 value with high demand rate according to SN 31920         | 1 000 000                                        |
| failure rate [FIT] with low demand rate according to SN 31920 | 100 FIT                                          |
| ISO 13849                                                     |                                                  |
| device type according to ISO 13849-1                          | 3                                                |
| overdimensioning according to ISO 13849-2 necessary           | Yes                                              |
| IEC 61508                                                     |                                                  |
| safety device type according to IEC 61508-2                   | Type A                                           |
| Electrical Safety                                             |                                                  |
| protection class IP on the front according to IEC 60529       | IP20                                             |
| touch protection on the front according to IEC 60529          | finger-safe, for vertical contact from the front |

#### Approvals Certificates

|                                                            |                          |
|------------------------------------------------------------|--------------------------|
| Environmental Product Declaration                          |                          |
| • global warming potential [CO2 eq] / during manufacturing | 5.88 kg                  |
| • global warming potential [CO2 eq] / during operation     | 102 kg                   |
| • global warming potential [CO2 eq] / after end of life    | -0.988 kg                |
| • global warming potential [CO2 eq] / total                | 107 kg                   |
| Environment                                                | General Product Approval |

[Environmental Confirmations](#)



[Miscellaneous](#)



|                          |     |                                          |
|--------------------------|-----|------------------------------------------|
| General Product Approval | EMV | Test Certificates                        |
|                          |     |                                          |
|                          |     | <a href="#">Special Test Certificate</a> |

|                                                    |                      |
|----------------------------------------------------|----------------------|
| Test Certificates                                  | Maritime application |
| <a href="#">Type Test Certificates/Test Report</a> |                      |
|                                                    |                      |
|                                                    |                      |
|                                                    |                      |
|                                                    |                      |

|                      |                               |                                          |
|----------------------|-------------------------------|------------------------------------------|
| Maritime application | other                         | Railway                                  |
|                      | <a href="#">Miscellaneous</a> | <a href="#">Confirmation</a>             |
|                      | <a href="#">Confirmation</a>  |                                          |
|                      |                               | <a href="#">Special Test Certificate</a> |

#### Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>  
Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>  
Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2037-3NP30>  
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3RT2037-3NP30>  
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2037-3NP30&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2037-3NP30&lang=en)  
Cax online generator  
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2037-3NP30>  
Kennlinien  
<https://curves.simar.siemens.com/curves/3RT2037-3NP30>



last modified:

7/22/2026

