SIEMENS

Data sheet 6ED1057-4CA00-0AA0



LOGO! contact 24 Switching module for direct switching of resistive loads up to 20 A and motors up to 4 kW, 24 V DC, 3 NO contacts+1 NC EAN: 4025515050742

Supply voltage	
Rated value (DC)	
● 24 V DC	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C
● max.	55 °C
Dimensions	
Width	36 mm
Height	72 mm
Depth	55 mm
Weights	
Weight, approx.	160 g
Classifications	

	Version	Classification
eClass	16	27-24-22-16
eClass	14	27-24-22-16
eClass	12	27-24-22-16
eClass	9.1	27-24-22-16
eClass	9	27-24-22-16
eClass	8	27-24-22-16
eClass	7.1	27-24-22-16
eClass	6	27-24-22-16
ETIM	10	EC001417
ETIM	9	EC001417
ETIM	8	EC001417
ETIM	7	EC001417
IDEA	4	3565
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	**Maritime application**

Subject to change without notice
© Copyright Siemens

Manufacturer Declaration

last modified: 5/22/2024

Subject to change without notice
© Copyright Siemens