SIEMENS

Data sheet for SIMOTICS S-1FT7



Figure similar

Article No. : 1FT7108-5AC71-1CA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	2,000 rpm
Number of poles	10
Rated torque (100 K)	50.0 Nm
Rated current	18.00 A
Static torque (60 K)	58.0 Nm
Static torque (100 K)	70.0 Nm
Stall current (60 K)	21.00 A
Stall current (100 K)	25.00 A
Rotor moment of inertia	248.00 kgcm²
Efficiency	93.0 %

Physical constants	
Torque constant	2.72 Nm/A
Voltage constant at 20° C	173.5 V/1000*min^{-1}
Winding resistance at 20° C	0.11 Ω
Rotary field inductance	3.1 mH
Electrical time constant	28.00 ms
Mechanical time constant	1.00 ms
Thermal time constant	95 min
Shaft torsional stiffness	126,000 Nm/rad
Net weight of the motor	59.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP67
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Safety Integrated - Suitable encoder	Yes
Electrical connection	Connector turnable
Connector size	1.5

Optimum operating point	
Optimum speed	2,000 rpm
Optimum power	10.5 kW

Limiting data	
Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	3,310 rpm
Maximum torque	280.0 Nm
Maximum current	120.00 A

Recommended Motor Module	
Rated inverter current	30.00 A
Maximum inverter current	90.00 A
Maximum torque	215.0 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens