SIEMENS

## Data sheet for SIMOTICS S-1FK2

**Article No. :** **1FK2205-4AF10-1MA0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :


| Basic motor data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor, Natural cooling, IP64 |
| Motor type | Compact |
| Static torque | 6.00 Nm |
| Static current | 4.7 A |
| Maximum torque | 18.00 Nm |
| Maximum current | 15.1 A |
| Maximum speed | 6,000 rpm |
| Rotor moment of inertia | 6.0000 kgcm² |
| Weight | 6.2 kg |

| Rated data | |
|---|---|
| SINAMICS S210, 3AC 400V | |
| Rated speed | 3,000 rpm |
| Rated torque | 4.60 Nm |
| Rated current | 3.8 A |
| Rated power | 1.45 kW |

| Encoder system | |
|---|---|
| Encoder system | Encoder AM22DQC: Absolute encoder 22 bit + 12 bit multiturn |
| Safety Integrated - Suitable encoder | Yes |

| Motor connection | |
|---|---|
| Connection type | OCC for S210 |
| Connector size OCC | M17 |

| Mechanical data | |
|---|---|
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Vibration severity grade | Grade A |
| Shaft height | 48 |
| Flange size (AB) | 95 mm |
| Centering ring (N) | 80 mm |
| Hole circle (M) | 100 mm |
| Screw-on hole (S) | 6.5 mm |
| Overall length (LB) | 220 mm |
| Diameter of shaft (D) | 19 mm |
| Length of shaft (E) | 40 mm |
| Length of flange diagonal (P) | 120 mm |
| Shaft end | Fitted key |
| Color of the housing | Standard (Anthracite, similar to RAL 7016) |




| Holding brake | |
|---|---|
| Holding torque | 8.00 Nm |
| Average dynamic torque | 5.00 Nm |
| Opening time | 35 ms |
| Closing time | 20 ms |
| Maximum single switching energy [1)] | 570 J |
| Service life, operating energy | 284,000 J |
| Holding current[2)] | 0.3 A |
| Break-induced current for 500 ms[2)] | 1.1 A |

[1)] Up to three consecutive emergency stops and up to 25% of all emergency stops as a Wmax high energy stop possible.

[2)] Typcial value for 20°C ambient temperature. At -15°C the break-induced currents can be increased by up to 30%.

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens