SIEMENS

Data sheet 3RK1903-0CH10



Figure similar

2 DI 24 V DC COM Control Module for ET200S High Feature Starter for ET 200S Failsafe Starter for local input functions with COM interface for PC cable 6ED1057-1 AA00-0BA0

Substance Prohibitance (day/month/year)	05/01/2012
SVHC substance name	Lead monoxide (lead oxide) CAS-No. 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1
Net Weight	0.014 kg
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe
Ambient conditions	
ambient temperature	
● during operation	-40 ... +80 °C
● during storage	0 ... 60 °C

Approvals Certificates

General Product Approval	EMV	other
UL, EAC, CE EG-Konf., UKCA, RCM		Confirmation

other	Environment
产品合格 QC PASS	Environmental Con-firmations

Further information


Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1903-0CH10
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1903-0CH10
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK1903-0CH10
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

Subject to change without notice
© Copyright Siemens

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1903-0CH10&lang=en

Kennlinien

https://curves.simaris.siemens.com/curves/3RK1903-0CH10



last modified: 4/2/2025

Subject to change without notice
© Copyright Siemens