AB-C5-M12FS-PB-TR-SH

Article No.: 22261001

Terminating resistor; PROFIBUS DP; M 12; Socket; Shielded: Yes





Details

Benefits

- Cost efficient termination of a bus systems
- Space-saving due to compact dimensions
- Robust design

Application

- Mechanical and plant engineering

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without surcharges and VAT. Sales only to business customers.

Remarks

© (2026) Lapp Group - all rights reserved.

Technical Data

General information

Product type	Terminating resistor
Weight	0.034 kg
Delivery Unit	1
valid fieldbus or Ethernet system	PROFIBUS DP
customs code	85369010

Electrical parameters

Product design

Shielded	Yes
Number of contacts	5
Status display	No
Connector housing design	Straight
Coded	Yes
With thread	Yes
Connector format	M 12
Connector type	Socket
Coding type	B-coded
Connector housing angle	180 °

Product features

UV-resistant	No
Vibration protection	Yes

Certifications and standards

CE marking	No
EAC-certified	Not required
EAC certification number	Отказное письмо № 39
UL recognized	No

© (2026) Lapp Group - all rights reserved.

UL listed	No
cUR recognised	No
cUL listed	No
CSA certified	No

© (2026) Lapp Group - all rights reserved.

EPIC® DATA PB TR M12

Article No.	Name	Shielded
22260722	AB-C4-M12MS-PB-TR	No
22261001	AB-C5-M12FS-PB-TR-SH	Yes

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.