SIEMENS

Data sheet 6ES7408-1TB00-0XA0

********** spare part ********* SIMATIC S7-400, fan subassembly for rack with 18 slots, 120/230 V AC



Figure similar

Supply voltage	
Rated value (AC)	
● 120 V AC	Yes
● 230 V AC	Yes
Line frequency	
● permissible range, lower limit	47 Hz
● permissible range, upper limit	63 Hz
Input current	
Inrush current, typ.	0.6 A at rated voltage 230 VAC: 1.15 A: at rated voltage 120 VAC
Power loss	
Power loss, max.	20 W
Digital outputs	
Relay outputs	
● Rated supply voltage of relay coil L+ (DC)	24 V
Switching capacity of contacts	
— with resistive load, max.	200 mA
Dimensions	
Width	482.5 mm
Height	109.5 mm
Depth	235 mm
Weights	
Weight, approx.	2 000 g
Classifications	

	Version	Classification
eClass	16	27-24-22-92
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Subject to change without notice
© Copyright Siemens

IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval





Miscellaneous





General Product Approval			EMV		Maritime application
China RoHS	Miscellaneous	Manufacturer Declaration			

Maritime application







CCS (China Classification Society)

last modified: 7/16/2026

Subject to change without notice
© Copyright Siemens