SIEMENS

## Data sheet 3VL3725-1AA36-0AA0

circuit breaker VL250N without Electronic Trip Unit standard breaking capacity Icu=55kA/415V AC, 3-pole In=< 250A, rated current with screw terminal connections for switching unit and Electronic Trip Unit

| | |
|---|---|
| Weight | 1.946 kg |
| Net Weight | 1.776 kg |

### Approvals / Certificates

| Environment | | General Product Approval | | | |
|---|---|---|---|---|---|
| Environmental Confirmations | Environmental Confirmations | | | Confirmation | |

| Test Certificates | other | | | |
|---|---|---|---|---|
| Special Test Certificate | Miscellaneous | Confirmation | | Miscellaneous |

### Further information

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012
**Information- and Downloadcenter (catalogues, leaflets,...)**
https://www.siemens.com/energy-automation
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3725-1AA36-0AA0
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3VL3725-1AA36-0AA0
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3725-1AA36-0AA0
**CAx-Online-Generator**
https://www.siemens.com/cax
**Kennlinien**
https://curves.simaris.siemens.com/curves/3VL3725-1AA36-0AA0

**last modified:** 4/4/2025


Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens