SIEMENS

Data sheet 3VL1705-1EA43-0AA0

	circuit breaker VL160X N standard breaking capacity Icu=55kA, 415V AC 4-pole, line protection Trip Unit TM, LI In=50A, rated current Ir=50A, overload protection II=600A, short-circuit prot. N protected without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes
Weight	2.933 kg
Net Weight	2.933 kg

Approvals / Certificates

Environment		General Product Approval	
Environmental Confirmations	Environmental Confirmations		Confirmation

Test Certificates	other		
Special Test Certificate	Miscellaneous	Confirmation	Miscellaneous

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1705-1EA43-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL1705-1EA43-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1705-1EA43-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL1705-1EA43-0AA0

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens