SIEMENS

Data sheet 6ES7292-0AA50-1AA0



SIMATIC HMI IRD400 Infrared display unit PROFINET interface 3x 7-7-segment display

General information	
Product type designation	IRD400 infrared display unit
Display	
Design of display	3 x seven-segment display
Screen diagonal	3.8 in
Display width	140 mm
Display height	116 mm
Number of colors	1; red
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	1.2 A
Interfaces	
Number of industrial Ethernet interfaces	2
Classifications	

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	

Subject to change without notice
© Copyright Siemens

Manufacturer Declaration

China RoHS

EMV

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW

last modified: 8/22/2025

Subject to change without notice
© Copyright Siemens