SIEMENS

## Data sheet 6ES7923-0BD00-0CB0



Figure similar

CONNECTING CABLE S7 UNSHIELDED 3.0M

Connecting cable unshielded for SIMATIC S7-300/1500 between front connector module and Connection module 16x0.14 mm2 with IDC connectors, Length = 3.0 m

| | |
|---|---|
| Technical Product Detail Page | https://i.siemens.com/1P6ES7923-0BD00-0CB0 |
| target system | SIMATIC S7-300 / 1500 |
| suitability for use | Digital I/O modules |
| suitability for interaction | |
| ● input card PLC | Yes |
| ● PLC output card | Yes |
| suitability for use | |
| ● digital signal transmission | Yes |
| ● analog signal transmission | No |
| product brand name | SIMATIC Top connect |
| product type designation | Fully modular connection |
| product designation | Pre-assembled round cable |
| **electrical data** | |
| operating voltage / at DC | |
| ● rated value | 24 V |
| ● maximum | 60 V |
| **connection method** | |
| design of cable | Round cable |
| number of channels | 8 |
| wire length | 3 m |
| conductor cross section / rated value | 0.14 mm² |
| Product component / with shield | No |
| number of poles | 16 |
| ● at the 1st interface | 16; cable side front connector module |
| ● at the 2nd interface | 16; on the connection module |
| connector type | IDC connector |
| type of electrical connection / on enclosure | Connector strip |
| type of electrical connection / in the field | Connector strip |
| **standards, specifications, approvals** | |
| certificate of suitability | |
| ● cULus approval | No |
| **Environmental Product Declaration** | |
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] | |
| ● total | 2.904 kg |
| ● during manufacturing | 2.824 kg |
| ● during operation | 0 kg |
| ● after end of life | 0.007 kg |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **ambient conditions** | |
| ambient temperature | |
| ● during operation | 0 ... 60 °C |
| ● during storage | -30 ... +70 |
| **mechanical data** | |
| outer diameter / of cable sheath | 6.5 mm |
| material / of the connection cable sheath | PVC |
| color / of cable sheath | Black |
| net weight | 0.235 kg |
| **internet links** | |
| internet link | |
| ● to website: Industry Mall | https://mall.industry.siemens.com |
| ● to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| ● to web page: system cabling | https://siemens.com/simatic-top-connect |
| ● to website: Industry Online Support | https://support.industry.siemens.com |
| **additional information** | |
| other information | technical specifications apply to rated input voltage values and +25 °C ambient temperature (if not otherwise specified) |
| marketing text | The 16-pin round cable (unshielded) with a length of 3m represents the link between the front connector and connection module. This pre-assembled cable enables a trouble-free and safe signal flow. Even complex installations remain manageable and can be checked in the shortest possible time, which makes maintenance and expansion affordable. This pre-assembled connecting cable is part of the fully modular SIMATIC TOP connect connection for the fastest and safest system cabling. In addition to low wiring costs, error sources in cabling can be significantly reduced. Sensors and actuators from the peripherals are combined with the connection modules of SIMATIC TOP connect and connected to the SIMATIC S7-1500 via cable and front plug-in module. |

**last modified:** 8/28/2026


Subject to change without notice
© Copyright Siemens