SIEMENS

Data sheet 6DL1193-6BH00-0RM0

Siemens EcoTech

SIMATIC ET 200SP HA, holder module IM redundant, support for holding two redundant interface modules of the SIMATIC ET 200SP HA, including server module

General information	
Product type designation	Carrier module IM redundant
Product function	
● I&M data	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
● Number of slots	2
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	100 mm
Height	204 mm
Depth	29 mm; measured without power plug
Weights	
Weight, approx.	224 g
Classifications	

	Version	Classification
eClass	16	27-24-26-07
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates	
General Product Approval	

Subject to change without notice
© Copyright Siemens

Miscellaneous

Declaration of Conformity

General Product Approval

China RoHS

Miscellaneous

Manufacturer Declaration

For use in hazardous locations

Declaration of Conformity

For use in hazardous locations

Maritime application

Miscellaneous

NK / Nippon Kaiji Kyokai

Maritime application

Environment

CCS (China Classification Society)

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens