SIEMENS

Data sheet 3UF7941-0AA00-0

USB PC cable for connection to the USB interface of a PC length 2.5 m, for communication with SIMOCODE pro or SIRIUS 3RW44 soft starter or safety system 3SK2 and 3RK3 via the system interface



General technical data	
product brand name	SIMOCODE
product designation	USB PC cable
ambient temperature	
● during storage	-40 ... +80 °C
● during operation	-25 ... +60 °C
● during transport	-40 ... +80 °C

Certificates/ approvals

General Product Approval	EMV	Test Certificates	Maritime application
		Type Test Certificates/Test Report	

other	Environment	Industrial Communication
Confirmation	Environmental Confirmations	

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7941-0AA00-0
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7941-0AA00-0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3UF7941-0AA00-0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7941-0AA00-0&lang=en

Subject to change without notice
© Copyright Siemens



© Copyright Siemens