SIEMENS

Data sheet 3VL2716-3DC33-0AA0

circuit breaker VL160L very high breaking capacity Icu=100kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=160A, rated current IR=125...160A, overload protection, II=800...1600A, short-circuit protection without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.57 kg
Net Weight	2.57 kg

Approvals / Certificates

Environment		General Product Approval			
Environmental Confirmations	Environmental Confirmations			Confirmation	

Test Certificates	other			
Special Test Certificate	Miscellaneous	Confirmation		Miscellaneous

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2716-3DC33-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL2716-3DC33-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2716-3DC33-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL2716-3DC33-0AA0

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens