


Data sheet:

Web Thermometer NTC

Article no.: 57714



This article has been replaced by model #57114.

Measure, log and report...

The Web Thermometer is a measuring device which monitors [temperatures](#) and makes the values available in the network. The device includes an integrated data logger and numerous Web and network services for manual querying of the measurements or provides autonomous sending of messages.

Properties

Sensor:

- **NTC temperature sensor:**
 - Measuring range: -45°C...75°C

Connectivity:

- **Intuitive Web interface** for simpler configuration
- **Monitor temperatures and trends from a browser**
- **Alarm and reporting function:**
 - E-mail for alarm or reporting functions
 - SNMP polling / alarm traps
 - Configure up to 12 alarm messages
- **Dynamic integration into other Web sites:**
 - Direct access to current measurement values, e.g. JavaScript (AJAX).
- **Current Industry 4.0 protocols:**
 - OPC UA, REST and [MQTT](#) support
- **Additional software interfaces for incorporating into your systems/databases:**
 - SNMPv1, SNMPv2c, SNMPv3
 - Modbus-TCP
 - OPC UA, OPC DA
 - Syslog
 - Sensobase (database integration via ODBC)
 - TCP and UDP sockets, client and server
 - FTP (data logging)
- **Possible applications:**
 - Monitor temperatures in the server room, network cabinet or office
 - Logging of measurements via FTP, Excel file, email attachment and internal memory
 - Green IT: Monitor efficiency of the server room climate control

Data logger:

- **Internal data logger**
 - Memory capacity: min. 16 weeks, max. 20 years
 - Save frequency: 15s, 30s, 1m, 5m, 15m, 60m
- **Document measurement data online in the [W&T Cloud](#) and access** from anywhere in the world

- **Internal clock**
 - Time synchronization via time server calibration
 - Battery-backed device clock

Standards & more

- optional: **ISO factory calibration** per DIN EN ISO/IEC 17025
 - with calibration certificate for verified documentation of the measured value deviations
 - Valid for 12 months
- optional: **DAkkS/DKD calibration** per DIN EN ISO/IEC 17025
 - with calibration certificate for verified traceability to national standards
 - Valid for 12 months
- **Supply voltage via Power-over-Ethernet (PoE)**
 - Phantom power using data pairs
 - Power over unused wire pairs
 - External power supply is an alternative
- **Conforms to standards both in office and industrial environments:**
 - High noise resistance per EN 61000-6-2
 - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3
- **5 year guarantee**

Wish for something!

[Your suggestions for improvement and additions](#)


Technical data

Connections and displays:

Temperature sensor:	NTC type DB9 receptacle Cable length: 1m (cannot be extended)
Network:	10/100BaseT Autosensing/Auto-MDIX RJ45 IPv6 on request
Galvanic isolation:	Network connection min. 1500 V
Power supply:	Power-over-Ethernet (PoE) or DC 12V .. 48V (+/-10%) or AC 18Veff .. 30Veff (+/-10%)
Supply connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Current consumption:	PoE Class 1 (0.44 - 3.84W) typ. 62mA @24VDC, 80mA @20VAC, max. 70mA @24VDC, 40mA @48VDC
Displays:	1 LED Power 2 LEDs network status 4 LEDs Status and Error

Measuring unit:

Sensor:	NTC 10k
Measuring range:	-45°C...75°C
Resolution:	1/10°C



Maximum measuring error: $\pm 0.3^{\circ}\text{C}$, $\pm 5.1\%$
(measuring unit + sensor)

Measuring frequency: 4 seconds

Storage frequency: 15s, 30s, 1m, 5m, 15m, 60m

Memory depth (4MB): min. 16 weeks, max. 20 years

Housing and other data:

Housing:	Plastic compact housing for top-hat rail mount 105x22x75mm (LxWxH)
Enclosure rating:	IP20
Weight:	approx. 200g
Ambient temperature	Storage: -40..+70°C Operating: Non-contiguous mounting: 0 .. +60°C contiguous mounting: 0 .. +50°C
Permissible relative humidity:	0..95% RH (non-condensing)
Ambient operating temperature:	0 .. +60°C
Scope of delivery:	1x Web-Thermometer NTC 1x NTC Sensor, 1m 1x Quick Guide

Accessories

*Net unit price for
commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	21.00 €
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00 €
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	33.00 €

Storage and Visualization

logic.hub	50506	598.00 €
-----------	-----------------------	----------

Measuring - Accessories

ISO factory calibration, 1x 3 temperature points for complete device with calibration certificate, valid for 12 months Delivery time approx. 10-14 days (This article cannot be ordered as a sample.)	57013	218.00 €
Accredited DAkkS/DKD calibration, 1x 3 temperature points for complete device with calibration certificate, valid for 12 months Delivery time approx. 10-14 days (This article cannot be ordered as a sample.)	57029	328.00 €

Mechanical Accessories

Mounting bracket for wall mounting	58812	11.20 €
19" DIN rail	58813	21.00 €

Supplementary network products

Ethernet Switch Gigabit Industry, 4 Ports	55614	148.00 €
---	-----------------------	----------

Software

WuTility	00104	free
OPC Server	00103	free
Sensobase®	00107	free
Web-IO2Go (app for iOS)	57700	free

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

W&T

www.WuT.de

Wiesemann & Theis GmbH

Porschestra. 12

42279 Wuppertal

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)

Fax: +49 202/2680-265

info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.