SIEMENS

Data sheet 7KN1111-0MC00



Powercenter 1100 up to 24 SENTRON COM devices, 24 V DC please consider wireless approval! list of countries: see certificates

Model	
product brand name	SENTRON
product designation	Data transceiver
design of the product	data transceiver for SENTRON COM circuit protection devices via radio protocol
product type designation	Powercenter 1100
design of the housing	DIN rail device
General technical data	
degree of pollution according to EN 60664-1	2
number of interfaces according to wireless	wireless, Bluetooth
guideline via radio-controlled system	2014/53/EU
frequency with radio transmission minimum	2 402 MHz
frequency with radio transmission maximum	2 480 MHz
vibration resistance under ambient conditions according to IEC 60068-2-6	1-6 Hz, 15 mm, 6-500 Hz, 20 m/s²
consumed current maximum	100 mA
Supply voltage	
supply voltage at DC rated value	
● minimum	19.2 V
● maximum	28.8 V
type of voltage of the supply voltage	24 V DC SELV
Protection class	
protection class IP	IP20
protection class IP on the front	IP20
Suitability	
suitability for use	SENTRON COM circuit protection devices (radio)
suitability for use safety-related function	Yes
Communication	
number of interfaces according to wireless	2
standard for wireless communication bluetooth note	V5.1,
number of interfaces according to Industrial Ethernet	2
protocol is supported	
● MODBUS protocol	Yes
● other protocols	Yes
Number	
number of supported devices	24
type of terminals screwless	yes
connectable conductor cross-section	
● minimum	0.2 mm²

Subject to change without notice
© Copyright Siemens

● maximum	1.5 mm²
Mechanical Design	
height	90 mm
width	18 mm
depth	70 mm
fastening method rail mounting	Yes
Net Weight	70 g
Environmental conditions	
relative humidity with condensation according to IEC 60068-2-38 maximum	95 %
relative humidity with condensation according to IEC 60068-2-38	RH incl. condensation/frost (no commissioning with condensation)
shock acceleration during operation according to EN 60068-2-27	150 m/s², 11 ms
ambient temperature during operation	
● minimum	-25 °C
● maximum	60 °C
ambient temperature during storage and transport	
● minimum	-40 °C
● maximum	80 °C

Approvals Certificates


Environment	General Product Approval			Radio Equipment Type Approval Certificate
Environmental Confirmations		Confirmation		Miscellaneous


Radio Equipment Type Approval Certificate	other	
Miscellaneous	Confirmation	


Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KN1111-0MC00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/7KN1111-0MC00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KN1111-0MC00
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/7KN1111-0MC00


Subject to change without notice
© Copyright Siemens







Subject to change without notice
© Copyright Siemens



last modified: 8/6/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens