SIEMENS

Data sheet 6ES7292-0CA50-0AA0



SIMATIC S7-1200, EMS400S, IR-RC infrared remote control

Control elements	
Keyboard	
● Design	Membrane keyboard
● Color of the buttons	gray
● Function keys	
— Number of function keys	4
— Programmable	Yes
● Number pad	Yes
● status LED displays	Yes
Connection type	
● Range without cables	10 m
Supply voltage	
Rated value (DC)	3 V; 2x AA batteries
Battery	
Design	
● AA	Yes
Interfaces	
Device-side interface	Infrared sender
Degree and class of protection	
IP (at the front)	IP65
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	60 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	95 %
Dimensions	
Width	85 mm
Height	152 mm
Depth	35 mm
Weights	
Weight, approx.	200 g
Classifications	

Subject to change without notice
© Copyright Siemens

	Version	Classification
eClass	16	27-24-22-92
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

EMV

EMV

last modified: 8/22/2025

Subject to change without notice
© Copyright Siemens