SIEMENS

Data sheet for SIMOTICS S-1FT2

Article No. : **1FT2103-2AH10-1SB0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :


Basic motor data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP64
Motor type	High Dynamic
Static torque	0.64 Nm
Static current	1.1 A
Maximum torque	1.95 Nm
Maximum current	4.0 A
Maximum speed	8,000 rpm
Rotor moment of inertia	0.1120 kgcm²
Weight	1.6 kg

Rated data	
SINAMICS S120, BLM/SLM 3AC 400V	
Rated speed	4,500 rpm
Rated torque	0.59 Nm
Rated current	1.1 A
Rated power	0.28 kW

Encoder system	
Encoder system	Encoder AS22DQC: Absolute encoder single turn 22 bit
Safety Integrated - Suitable encoder	Yes

Motor connection	
Connection type	Double cable connection for S120
Connector size power connector	M17
Connector size signal connector	M17

Mechanical data	
Design acc. to Code I	IM B5 (IM V1, IM V3)
Vibration severity grade	Grade A
Shaft height	30
Flange size (AB)	60 mm
Centering ring (N)	50 mm
Hole circle (M)	70 mm
Screw-on hole (S)	5.4 mm
Overall length (LB)	131 mm
Diameter of shaft (D)	14 mm
Length of shaft (E)	30 mm
Length of flange diagonal (P)	81 mm
Shaft end	Fitted key
Color of the housing	Standard (Anthracite, similar to RAL 7016)



Holding brake	
Holding torque	1.30 Nm
Average dynamic torque	1.30 Nm
Opening time	90 ms
Closing time	30 ms
Maximum single switching energy [1)]	62 J
Service life, operating energy	5,000 J
Rated current[2)]	0.4 A

[1)] Up to three consecutive emergency stops and up to 25% of all emergency stops as a Wmax high energy stop possible.

[2)] Typcial value for 20°C ambient temperature. At -15°C the break-induced currents can be increased by up to 30%.

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens