SIEMENS

Data sheet 4AV4110-2EB00-0A



Figure similar

power supply; phases: 1; Pn(kW): 0.24; Upri(V): 400-230+/-15; Usec(V DC): 24; Isec(A DC): 10; F(Hz): 50...60; vector group/shielding winding: II0 /0; protection class: I; temperature rise/insulation class: 40 /B; W(%): 5; IP00; connection: screw/flat-type connection; mounting: screws; EN 61558, EN 61131-2 >safety transformer<

General technical data		
product designation		4AV4110-2EB00-0A
product brand name		SIDAC
vector group		Ii0
certificate of suitability		CE
product function		
● temperature monitoring		No
● insulation monitoring		No
● short-circuit and overload proof		No
● varistor protective wiring		Yes
operating resource protection class		I
number of shielding windings		0
Inputs		
phase number of the inputs		1
type of current of the inputs		AC
input voltage		
● _1 rated value	V	415
● _2 rated value	V	400
● _3 rated value	V	385
● _4 rated value	V	245
● _5 rated value	V	230
● _6 rated value	V	215
electrical input frequency		
● minimum	Hz	50
● maximum	Hz	60
input voltage		
● minimum	V	193.5
● maximum	V	439.9
input current		
● _1 rated value	A	0.85
● _2 rated value	A	0.89
● _3 rated value	A	0.92
● _4 rated value	A	1.46
● _5 rated value	A	1.54
● _6 rated value	A	1.65
type of electrical connection at input for main current circuit		screw-type terminals / tab terminals
Outputs		

Subject to change without notice
© Copyright Siemens

type of current		
● _1 at output		DC
output voltage		
● _1 rated value	V	24
output voltage of the measurement signal at analog output at DC maximum	V	30
output voltage of the measurement signal at analog output at DC minimum	V	20.4
output current		
● _1 rated value	A	10
type of electrical connection at output for main current circuit		screw-type terminals / tab terminals
relative residual ripple		
● of the output voltage 1 for main current circuit maximum	%	5
Ambient conditions		
thermal class according to IEC 60085		B
ambient temperature rated value	°C	40
protection class IP		IP00
Mechanical data		
fastening method		screws
construction form of the iron core		EI 120/52
width	mm	120
height	mm	170
depth	mm	105

Certificates/ approvals

General Product Approval	other	Environment
	Confirmation	Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AV4110-2EB00-0A
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AV4110-2EB00-0A
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/4AV4110-2EB00-0A
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AV4110-2EB00-0A&lang=en

last modified: 9/3/2026

Subject to change without notice
© Copyright Siemens