SIEMENS

Data sheet BVP:034259

BD01-E FEEDER UNIT C/W TWO END FLANGES



Figure similar

Model	
product designation	feeder unit for BD01 busbar trunking system
operating voltage at AC	
● at 50 Hz rated value maximum	400 V
● at 60 Hz rated value minimum	400 V
● at 60 Hz rated value maximum	400 V
Protection class	
protection class IP	IP54, mit Zusatzausruestung: IP55
Main circuit	
operating frequency rated value	
● minimum	50 Hz
● maximum	60 Hz
operational current	
● for circuit 1 at AC at 50 Hz rated value maximum	100 A
● for circuit 1 at AC at 60 Hz rated value maximum	100 A
Connections	
connectable conductor cross-section in the feeder unit	
● minimum	6 mm²
● maximum	50 mm²
Mechanical Design	
height	104 mm
width	150 mm
length	260 mm
fastening method	ceiling / wall
Net Weight	1 kg
material of the busbar	copper
Approvals Certificates	
General Product Approval	

CE
EG-Konf.

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage

Subject to change without notice
© Copyright Siemens

https://support.industry.siemens.com/cs/ww/en/view/109995012

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=BVP:034259

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/BVP:034259

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:034259

CAx-Online-Generator
https://www.siemens.com/cax

Tender specifications
https://www.siemens.com/specifications

Kennlinien
https://curves.simaris.siemens.com/curves/BVP:034259

---

last modified: 9/2/2024

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens