SIEMENS

# Data sheet for Output reactor

**Article No. :** **6SE6400-3TC05-4DD0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Rated data | |
|---|---|
| Rated current | 68.00 A |
| Power loss | 0.197 kW |

| Electrical data | |
|---|---|
| Inductance | 0.23 mH |

| Mechanical data | |
|---|---|
| Degree of protection | IP00 |
| Net weight | 11.3 kg (24.91 lb) |
| **Dimensions** | |
| Width | 225 mm (8.86 in) |
| Height | 210 mm (8.27 in) |
| Depth | 140 mm (5.51 in) |

| Connections | |
|---|---|
| **Power connection Power Module** | |
| Version | flat connector for cable lug M6 |
| **Power connection motor** | |
| Version | Flange connection for cable lug M6 |
| **Max. motor cable length** | |
| **3 AC 380 V -10 % ... 400 V** | |
| Shielded | 200 m |
| Unshielded | 300 m |
| **3 AC 401 V ... 480 V +10 %** | |
| Shielded | 200 m |
| Unshielded | 300 m |
| **PE connection** | |
| Version | M6 screw |

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens