SIEMENS

Data sheet 6ES7655-5DX40-2AA0

Active field distributor AFD4 for standard mounting rail mounting without enclosure for PROFIBUS PA for foundation Fieldbus H1, 4 short circuit-proof spur lines with bounce protection logic Automatic bus termination for line and ring topology for extended temperature range Degree of protection IP20



General information	
Product function	
● Repeater function	No
Supply voltage	
permissible range, lower limit (DC)	16 V
permissible range, upper limit (DC)	32 V
Input current	
Current consumption (in no-load operation), typ.	24 mA; 54 mA at the end of the cable
Power loss	
Power loss, typ.	384 mW
Power loss, max.	3.2 W
Interfaces	
PROFIBUS PA	
● Transmission rate, max.	31.25 kbit/s
Protocols	
PROFIBUS PA	Yes
FOUNDATION Fieldbus H1	Yes
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	No
Diagnostics function	Yes
Diagnostics indication LED	
● Main line status	Yes
● Spur line status/fault	Yes
● automatic bus termination	Yes
Potential separation	
between main line and spur lines	No
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Use in hazardous areas	
● ATEX Zone 1	No
● ATEX Zone 21	No
● ATEX Zone 2	Yes
● ATEX Zone 22	Yes
● FM Class I Zone 1	No
● FM Class I Zone 2, Division 2	Yes
Ambient conditions	

Subject to change without notice
© Copyright Siemens

Ambient temperature during operation	
● min.	-40 °C
● max.	70 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Connection method	
Main line	
● Number of main lines	2
● Design of terminals	Screw terminal block
● Type of cable	Type A
● Conductor cross-section, min.	0.2 mm²
● Conductor cross-section, max.	2.5 mm²
● automatic bus termination	Yes
● permissible main line current	1 A
Spur line	
● Number of spur lines	4
● Type of cable	Type A
● Conductor cross-section, min.	0.2 mm²
● Conductor cross-section, max.	2.5 mm²
● Number of connectable field devices	4
● total current output to field devices, max.	240 mA
● Current limitation per field device, max.	60 mA
● Short-circuit current (test current); max.	6 mA
● intrinsically safe according to FISCO model	No
● Debounce logic	Yes
Dimensions	
Width	220 mm
Height	120 mm
Depth	83 mm
Weights	
Weight, approx.	1 000 g

Classifications

	Version	Classification
eClass	16	27-24-26-08
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

China RoHS

Subject to change without notice
© Copyright Siemens

General Product Approval		For use in hazardous locations			
Miscellaneous	Manufacturer Declaration	ATEX	IECEx	Type Examination Certificate	FM

For use in hazardous locations		Environment
CCC	INMETRO	EPD

last modified: 9/11/2026

Subject to change without notice
© Copyright Siemens