SIEMENS

## Data sheet 3LD3354-0TK53



Load disconnector 3LD3, Iu 40 A Main switch 3-pole Rated operating capacity at AC-23 A at 400 V 18.5 kW Front plate mounting Basic switch with Central hole mounting 22.5mm Toggle drive red / yellow 66x66 mm

| | |
|---|---|
| **Model** | |
| **product brand name** | SENTRON |
| **product designation** | Switch disconnector |
| **design of the product** | EMERGENCY-OFF switch |
| **display version for switch position indicator manual operation** | 1 ON - 0 OFF |
| **type of switch** | front mounted |
| **design of the actuating element** | Short rotary knob |
| **color of the actuating element** | red |
| **design of handle** | rotary operating mechanism, red/yellow |
| **General technical data** | |
| **number of poles** | 3 |
| **number of poles note** | 3 |
| **mechanical service life (operating cycles) typical** | 100 000 |
| electrical endurance (operating cycles) | |
| ● at AC-23 A at 690 V | 6 000 |
| **operating frequency maximum** | 50 1/h |
| **degree of pollution** | 3 |
| **Voltage** | |
| insulation voltage rated value | 690 V |
| **surge voltage resistance rated value** | 6 kV |
| **operating voltage** | |
| ● at AC rated value | 690 V |
| **operating frequency rated value** | |
| ● minimum | 50 Hz |
| ● maximum | 60 Hz |
| **Protection class** | |
| **protection class IP** | IP65 |
| **degree of protection NEMA rating** | 1, 3R, 4X, 12 |
| protection class IP on the front | IP65 |
| **Dissipation** | |
| **power loss [W] for rated value of the current at AC in hot operating state per pole** | 0.62 W |
| **Main circuit** | |
| **operational current** | |
| ● at AC-21 at 690 V rated value | 40 A |
| ● at AC-21 A at 240 V rated value | 40 A |
| ● at AC-21 A at 400 V rated value | 40 A |
| ● at AC-21 A at 440 V rated value | 40 A |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● at AC-23 A at 400 V rated value | 36 A |
| **operating power** | |
| ● at AC-23 A at 240 V rated value | 7.5 kW |
| ● at AC-23 A at 400 V rated value | 19 kW |
| ● at AC-23 A at 440 V rated value | 15 kW |
| ● at AC-23 A at 690 V rated value | 15 kW |
| ● at AC-3 at 240 V rated value | 7.5 kW |
| ● at AC-3 at 400 V rated value | 12 kW |
| ● at AC-3 at 690 V rated value | 11.5 kW |
| **Auxiliary circuit** | |
| **number of CO contacts for auxiliary contacts** | 0 |
| **number of NC contacts for auxiliary contacts** | 0 |
| **number of NO contacts for auxiliary contacts** | 0 |
| **operating voltage of auxiliary contacts at AC maximum** | 500 V |
| **continuous current of the auxiliary contact rated value** | 10 A |
| **insulation voltage of the auxiliary switch rated value** | 500 V |
| **Suitability** | |
| **suitability for use main switch** | Yes |
| **suitability for use switch disconnector** | Yes |
| **suitability for use EMERGENCY OFF switch** | Yes |
| **suitability for use maintenance/repair switch** | Yes |
| **Product details** | |
| **special product feature** | Can be locked in zero position |
| **product feature can be locked into OFF position** | Yes |
| **Accessories** | |
| **product extension optional** | |
| ● motor drive | No |
| ● voltage trigger | No |
| **number of connectable NC contacts for auxiliary contacts attachable maximum** | 2 |
| **number of connectable NO contacts for auxiliary contacts attachable maximum** | 4 |
| **number of connectable CO contacts for auxiliary contacts attachable maximum** | 0 |
| **number of bracket locks maximum** | 3 |
| **hasp thickness of the bracket locks** | 4 ... 8 mm |
| **Short circuit** | |
| **conditional short-circuit current with line-side fuse protection** | |
| **● at 440 V by gG fuse rated value** | 10 kA |
| **● at 690 V by gG fuse rated value** | 6 kA |
| **let-through current with closed switch** | |
| **● at 240 V for combination switch + gG fuse maximum** | 5 kA |
| **● at 440 V for combination switch + gG fuse maximum** | 5 kA |
| **● at 690 V for combination switch + gG fuse maximum permissible** | 5 kA |
| **I2t value with closed switch** | |
| **● at 240 V for combination switch + gG fuse maximum** | 15 $kA^2 \cdot s$ |
| **● at 440 V for combination switch + gG fuse maximum** | 15 $kA^2 \cdot s$ |
| **● at 690 V for combination switch + gG fuse maximum** | 15 $kA^2 \cdot s$ |
| **design of the fuse link** | |
| **● for short-circuit protection of the main circuit required** | fuse gL/gG: 40 A |
| **● for short-circuit protection of the auxiliary switch required** | fuse gL/gG: 10 A |
| **operational current of upstream fuse rated value** | 40 A |
| **according UL** | |
| **operational current at AC according to UL 508/UL 60947-4-1 rated value** | 40 A |
| **operating voltage at AC at 50/60 Hz according to UL 508/UL 60947-4-1 rated value** | 600 V |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **active power [hp] at AC at 480 V according to UL 508/UL 60947-4-1 rated value** | 20 |
| **active power [hp] at AC at 600 V according to UL 508/UL 60947-4-1 rated value** | 20 |
| **short-time withstand current (SCCR) at 600 V according to UL 508/UL 60947-4-1** | 5 kA |
| **continuous current of upstream fuse according to UL rated value** | 50 A |
| **type of fuse according to UL** | RK5 |
| **Connections** | |
| **AWG number as coded connectable conductor cross section solid maximum** | |
| • | 6 |
| • | 14 |
| **type of connectable conductor cross-sections for copper conductor** | |
| • solid | 1x (2.5 to 16 mm²) |
| • finely stranded with core end processing | 1x (2.5...16 mm²) |
| • stranded | 1x (2.5 to 16 mm²) |
| **type of connectable conductor cross-sections for auxiliary contacts** | |
| • **solid** | 2x (0.75 ... 2.5 mm²), 1x 4 mm² |
| • **finely stranded with core end processing** | 2x (0.75 ... 1.5 mm²), 1x 2.5 mm² |
| • **stranded** | 2x (0.75 ... 2.5 mm²), 1x 4 mm² |
| type of electrical connection | |
| • **for main current circuit** | box terminal |
| • **for auxiliary contacts** | Box terminals |
| **Mechanical Design** | |
| **height** | 60 mm |
| **width** | 36 mm |
| **depth** | 114 mm |
| **type of device** | fixed mounting |
| **fastening method** | Built-in unit fixed-mounted version |
| **fastening method** | |
| • 4-hole front mounting | No |
| • front mounting with central attachment | Yes |
| • rail mounting | No |
| **Net Weight** | 237 g |
| **Environmental conditions** | |
| **ambient temperature during operation** | |
| • minimum | -25 °C |
| • maximum | 55 °C |
| **ambient temperature during storage** | |
| • minimum | -25 °C |
| • maximum | 55 °C |

**Approvals Certificates**


| Environment | | General Product Approval | | | |
|---|---|---|---|---|---|
| Environmental Con-firmations | Environmental Con-firmations | | | | |


| General Product Approval | | other | |
|---|---|---|---|
| Confirmation | | Confirmation | |


**Further information**



Subject to change without notice
© Copyright Siemens

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012
**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/lowvoltage/catalogs
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD3354-0TK53
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3LD3354-0TK53
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD3354-0TK53
**CAx-Online-Generator**
https://www.siemens.com/cax
**Tender specifications**
https://www.siemens.com/specifications
**Kennlinien**
https://curves.simaris.siemens.com/curves/3LD3354-0TK53




**last modified:** 8/28/2026


Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens