SIEMENS

Data sheet 6AV7674-1MC00-0AA0



Figure similar

indicator light for Extension Units, 22 mm, round, plastic, with integrated white LED, 6 light attachments (colorless, red, yellow, green, blue, black), without inscription, (incl. printed circuit board), scope of supply: 1 indicator light, 1 printed circuit board, 6 light attachments, including mounting accessories

General information	
Product type designation	Indicator light for Extension Unit
Control elements	
Version of actuating element	Flat lens
Shape of actuating element	Round
Illuminant	Yes; Can be illuminated
● Type of light source	SMT LED
● Color of light source	Translucent white (different colors are created using the colored disk supplied)
Installation type/mounting	
Mounting type	Threaded ring
Front mounting	Yes; Front plate attachment in an Extension Unit for 16:9 PRO devices
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption (rated value)	100 mA
EMC	
Emission of radio interference acc. to EN 55 011	
● Limit class A, for use in industrial areas	No
Degree and class of protection	
IP (at the front)	IP65 (on front) to EN60529 and NEMA4
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	Yes; Only in combination with Extension Unit
cULus	Yes; Only in combination with Extension Unit
RCM (formerly C-TICK)	Yes; Only in combination with Extension Unit
Suitable for safety functions	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	50 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	3 500 m
Relative humidity	
● Operation, max.	90 %

Subject to change without notice
© Copyright Siemens

● Condensation permissible	No
Mechanics/material	
Material	
● plastic	Yes
Material of the actuating element	plastic
Material of the front ring	plastic
Enclosure color (front)	Colorless
Color of the front ring	Silver metallic
Dimensions	
Height of housing front	9.85 mm
Mounting diameter	22.3 mm
Weights	
Weight (without packaging)	50 g
Weight (with packaging)	100 g
Scope of supply	
Delivery quantity in pieces	1
Components included	
● Number of colored lenses	5; colorless, red, yellow, green, blue
Other	
Target devices	Suitable for Extension Units of the 16:9 HMI/IPC PRO devices (refer to manual)

Classifications

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

China RoHS

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW

last modified: 6/3/2025

Subject to change without notice
© Copyright Siemens