SIEMENS

Data sheet 6AV6671-5CM00-0AX1

**** Spare part *** Does not correspond to the current version of the standard. Transponder V2 f. Mobile Panel 277(F) IWLAN V2 Attention! Not suitable for Mobile Panel 277(F) IWLAN V1!



Degree and class of protection	
IP degree of protection	IP65
Degree of protection according to NEMA	NEMA 4x, NEMA 12
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	
Ambient temperature during operation	
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	85 %
Dimensions	
Width	172 mm
Height	90 mm
Depth	38.5 mm
Weights	
Weight (without packaging)	0.3 kg
Classifications	

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Subject to change without notice
© Copyright Siemens

IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Manufacturer Declaration



last modified: 9/4/2024

Subject to change without notice
© Copyright Siemens