SIEMENS

Data sheet 3RK1922-2BQ00

Power jumper plug for power transmission (400 V) from ET 200pro maintenance switch module or motor starter to motor starter



Substance Prohibitance (day/month/year)	05/01/2012
Net Weight	185 g
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe
Ambient conditions	
ambient temperature	
● during operation	55 ... -25 °C
● during storage	-40 ... +70 °C

Approvals Certificates


General Product Approval	EMV	Test Certificates
cULus, EAC, CE EG-Konf., UKCA, RCM		Type Test Certificates/Test Report

other	Environment
Confirmation, 产品合格 QC PASS	Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1922-2BQ00
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1922-2BQ00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK1922-2BQ00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1922-2BQ00&lang=en
Kennlinien
https://curves.simaris.siemens.com/curves/3RK1922-2BQ00

Subject to change without notice
© Copyright Siemens



last modified: 4/2/2025

Subject to change without notice
© Copyright Siemens