SIEMENS

## Data sheet 3RS1725-1FW00



interface converter Phased-out product !!! For further information, please contact our sales department with Manual-Auto switch 24 V AC/DC, 3-way separation input: 0-10 V, 0/4-20 mA output: 0-10 V, 0/4-20 mA screw terminal

| | |
|---|---|
| **product brand name** | SIRIUS |
| **product designation** | multi-range converters |
| **General technical data** | |
| **design of the base unit** | switchable, active, with manual/automatic switch and single potentiometer as manual analog signal transmitter |
| **number of channels** | 1 |
| **consumed active power** | 0.75 W |
| insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 2 rated value | 300 V |
| **shock resistance according to IEC 60068-2-27** | 15 g / 11 ms |
| **vibration resistance according to IEC 60068-2-6** | 10 ... 55 Hz: 0.35 mm |
| **reference code according to IEC 81346-2** | T |
| **Substance Prohibitance (day/month/year)** | 07/01/2006 |
| **Net Weight** | 0.097 kg |
| **Supply voltage** | |
| **supply voltage at AC** | |
| ● at 50 Hz rated value | 24 ... 240 V |
| ● at 60 Hz rated value | 24 ... 240 V |
| **supply voltage at DC rated value** | 24 ... 240 V |
| supply voltage frequency rated value | 60 ... 50 Hz |
| **operating range factor supply voltage rated value** | |
| ● at AC at 50 Hz | 0.8 ... 1.1 |
| ● at AC at 60 Hz | 0.8 ... 1.1 |
| ● at DC | 0.7 ... 1.1 |
| **Precision** | |
| **relative metering precision** | 0.1 % |
| **relative linearity deviation** | 0.02 % |
| **temperature drift per °C** | 0.015 %/°C |
| **voltage ripple maximum** | 5 mV |
| **limit frequency** | 30 Hz |
| **settling time for 1 % deviation** | 30 ms |
| **rise time** | 10 ms |
| **Main circuit** | |
| **type of voltage** | AC/DC |
| **Inputs/ Outputs** | |
| **input voltage maximum** | 30 V |
| **property of the output short-circuit proof** | Yes |
| **overvoltage strength at the current output maximum** | 30 V |
| **type of signal at input** | 0 ... 10 V, 0 ... 20 mA, 4 ... 20 mA |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **type of signal at output** | 0 ... 10 V, 0 ... 20 mA, 4 ... 20 mA |
| **output load** | |
| ● at voltage output maximum | 1 kΩ |
| ● at the current output maximum | 400 Ω |
| **Galvanic isolation** | |
| **design of the electrical isolation** | 3 paths |
| **galvanic isolation** | |
| ● between input and output | Yes |
| ● between the voltage supply and other circuits | Yes |
| **Connections/ Terminals** | |
| **type of electrical connection** | screw terminal |
| **type of connectable conductor cross-sections** | |
| ● solid | 1x (0.5 ... 2.5 mm²) |
| ● finely stranded with core end processing | 2x (0.5 ... 2.5 mm²) |
| ● for AWG cables stranded | 2x (20 ... 16) |
| **connectable conductor cross-section** | |
| ● solid | 0.5 ... 2.5 mm² |
| ● finely stranded with core end processing | 0.5 ... 2.5 mm² |
| **AWG number as coded connectable conductor cross section** | |
| ● solid | 20 ... 14 |
| ● stranded | 20 ... 16 |
| **Installation/ mounting/ dimensions** | |
| **mounting position** | any |
| **fastening method** | snap-on mounting on 35 mm DIN rail according to DIN EN 50022 |
| **height** | 79 mm |
| **width** | 17.5 mm |
| **depth** | 90 mm |
| **Ambient conditions** | |
| **ambient temperature** | |
| ● during operation | -25 ... +60 °C |
| ● during storage | -40 ... +85 °C |
| ● during transport | -40 ... +85 °C |

**Approvals Certificates**

| Environment | General Product Approval | EMV | Test Certificates | other |
|---|---|---|---|---|
| Environmental Confirmations | | | Type Test Certificates/Test Report | Confirmation |


**other**

产品合格
QC PASS

**Further information**

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012
**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RS1725-1FW00
**Cax online generator**
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RS1725-1FW00
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3RS1725-1FW00
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**


Subject to change without notice
© Copyright Siemens




**last modified:** 4/4/2026


© Copyright Siemens