SIEMENS

Data sheet 3RK1911-1AJ32



Figure similar

ECOFAST hybrid field connection PROFIBUS CU/CU signal refresher CU
pin/socket IP65 front side CU D-SUB 9-pole Socket inside active (signal refresher)
Automatic baud rate search

General technical data	
Substance Prohibitance (day/month/year)	07/01/2006
Net Weight	0.283 kg

Approvals Certificates

Environment	General Product Approval
Environmental Confirmations	

EMV	other
	Confirmation

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1911-1AJ32
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1911-1AJ32
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK1911-1AJ32
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1911-1AJ32&lang=en

last modified: 4/2/2025

Subject to change without notice
© Copyright Siemens