SIEMENS

Data sheet 6ES7590-0CA00-0AA0

SIMATIC S7-1500 / ET 200MP; slot cover for the active backplane bus of S7-1500 for protection against ESD and for mechanical fixing on the S7-1500 mounting rail. unused slots must be provided with a slot cover! 5 units per packing unit

Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
● min.	-30 °C
● max.	60 °C
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	40 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Operation, min.	795 hPa
● Operation, max.	1 040 hPa
● Storage/transport, min.	660 hPa
● Storage/transport, max.	1 140 hPa
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Dimensions	
Width	25 mm
Height	150 mm
Depth	32 mm

Classifications

	Version	Classification
eClass	16	27-24-22-92
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Subject to change without notice
© Copyright Siemens

Manufacturer Declaration



Manufacturer Declaration

last modified: 8/2/2023

Subject to change without notice
© Copyright Siemens