SIEMENS

# Data sheet for SIMOTICS S-1FK7

## Article No. : 1FK7032-5AK71-1PA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 6,000 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 0.8 Nm |
| Rated current | 1.4 A |
| Static torque (60 K) | 0.85 Nm |
| Static torque (100 K) | 1.10 Nm |
| Stall current (60 K) | 1.40 A |
| Stall current (100 K) | 1.70 A |
| Moment of inertia | 0.610 kgcm² |
| Efficiency | 88.0 % |

| Physical constants | |
|---|---|
| Torque constant | 0.67 Nm/A |
| Voltage constant at 20° C | 45.0 V/1000*min⁻¹ |
| Winding resistance at 20° C | 5.20 Ω |
| Rotating field inductance | 18.5 mH |
| Electrical time constant | 3.60 ms |
| Mechanical time constant | 2.20 ms |
| Thermal time constant | 25 min |
| Shaft torsional stiffness | 6,500 Nm/rad |
| Net weight of the motor | 2.7 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 36 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.035 mm |
| Concentricity tolerance | 0.08 mm |
| Axial runout tolerance | 0.08 mm |
| Vibration severity grade | Grade A |
| Connector size | M23 |
| Degree of protection | IP64 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | KTY84 temperature sensor in the stator winding |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | without |
| Holding brake | without holding brake |
| Shaft end | Feather key |
| Encoder system | Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole) |

| Optimum operating point | |
|---|---|
| Optimum speed | 6,000 rpm |
| Optimum power | 0.5 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 10,000 rpm |
| Max. permissible speed (inverter) | 12,800 rpm |
| Maximum torque | 4.5 Nm |
| Maximum current | 7.0 A |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 3 A |
| Maximum inverter current | 6 A |
| Maximum torque | 3.90 Nm |

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens