SIEMENS

Data sheet for SIMOTICS S-1FK7

Article No. : **1FK7080-5AH71-1EG0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	4,500 rpm
Number of poles	8
Rated torque (100 K)	4.5 Nm
Rated current	4.7 A
Static torque (60 K)	6.60 Nm
Static torque (100 K)	8.00 Nm
Stall current (60 K)	6.10 A
Stall current (100 K)	7.40 A
Moment of inertia	15.000 kgcm²
Efficiency	92.0 %

Physical constants	
Torque constant	1.06 Nm/A
Voltage constant at 20° C	68.0 V/1000*min⁻¹
Winding resistance at 20° C	0.44 Ω
Rotating field inductance	6.3 mH
Electrical time constant	14.30 ms
Mechanical time constant	1.76 ms
Thermal time constant	40 min
Shaft torsional stiffness	126,000 Nm/rad
Net weight of the motor	10.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	80
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	M23
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface

Optimum operating point	
Optimum speed	4,000 rpm
Optimum power	2.4 kW

Limiting data	
Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	8,500 rpm
Maximum torque	25.0 Nm
Maximum current	25.0 A

Recommended Motor Module	
Rated inverter current	9 A
Maximum inverter current	18 A
Maximum torque	19.10 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens