SIEMENS

Data sheet 6GT2600-4AB00

product type designation	**MDS D460 transponder**
	Transponder MDS D460 for RF200/RF300 ISO/MOBY D PILL ISO 15693, Chip type FUJITSU MB89R118, 2000 byte FRAM User memory 16x 3 mm (DxH); Minimum order quantity 50 units.



suitability for operation	RF200, RF300, MOBY D
product brand name	SIMATIC RF
Technical Product Detail Page	https://i.siemens.com/1P6GT2600-4AB00
radio frequencies	
operating frequency / rated value	13.56 MHz
range / maximum	160 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	ISO 15693
transfer rate / with radio transmission / maximum	26.5 kbit/s
product feature / multitag-capable	Yes
electrical data	
product component / backup battery	No
memory	
type of memory	FRAM
storage capacity / of the user memory	2000 byte
type of memory organization	UID (fixed code) 8 bytes, user memory 2000 bytes, configuration memory 40 bytes
number of read cycles / at ambient temperature < 40 °C / maximum	1E+12
number of write cycles / at ambient temperature < 40 °C / maximum	1E+12
data retention time / at ambient temperature < 40 °C / not less than	10 a
property of memory	Block-by-block write protection of the user memory
type of transponder chip used	Fujitsu MB89R118
mechanical data	
material	PPS
color	black
mounting distance / relating to metal surfaces / recommended / minimum	10 mm
ambient conditions	
ambient temperature	
• during read/write access	-25 ... +85 °C
• outside the read/write area	-40 ... +100 °C
• during storage	-40 ... +100 °C
protection class IP	IP67/IPx9K
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
shock acceleration	500 m/s²
vibrational acceleration	200 m/s²

Subject to change without notice
© Copyright Siemens

design, dimensions and weights	
height	3 mm
diameter	16 mm
net weight	3 g
fastening method	patching, gluing
product features, product functions, product components / general	
product feature	
● printable	No
standards, specifications, approvals	
certificate of suitability	
● IECEx	No
MTBF	228 a
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	0.93 kg
● during manufacturing	0.88 kg
● during operation	0.00041 kg
● after end of life	0.05 kg
accessories	
accessories	Mounting support and spacer
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: identification and localization systems	https://www.siemens.com/ident
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

China RoHS | Manufacturer Declaration | Miscellaneous

General Product Approval	EMV	Environment

Subject to change without notice
© Copyright Siemens

Manufacturer Declaration

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens